

Cable semi-rígido (50 Ohms)

Semi-rigid cable (50 Ohms)



UT-86 (RG-405/U)							<i>GROUP</i>	<i>ALFA'R CODE</i> CÓDIGO ALFA'R	
							GRUPO		
							22X	A-CAB-22X-50	
Ω	<i>center cond.</i>	cond. central	<i>dielectric</i>	dieléctrico	<i>screen</i>	pantalla	<i>jacket</i>		
	material	\emptyset	material	\emptyset	material	\emptyset	material	\emptyset	
50±1.5	Cu	0.51 [.020]	PTFE	1.68 [.066]	Cu	2.2 [.087]	--	--	

GHz	1	2	4	7	10	20
dB/100mts	65	95	140	180	220	310
Watts	160	110	70	50	40	30

UT-141 (RG-402/U)							<i>GROUP</i>	<i>ALFA'R CODE</i> CÓDIGO ALFA'R	
							GRUPO		
							36X	A-CAB-36X-50	
Ω	<i>center cond.</i>	cond. central	<i>dielectric</i>	dieléctrico	<i>screen</i>	pantalla	<i>jacket</i>		
	material	\emptyset	material	\emptyset	material	\emptyset	material	\emptyset	
50±1	Cu	0.92 [.036]	PTFE	2.99 [.118]	Cu	3.58 [.141]	--	--	

GHz	1	2	4	7	10	20
dB/100mts	35	52	80	125	160	200
Watts	600	390	250	180	140	100

UT-250 (RG-401/U)							<i>GROUP</i>	<i>ALFA'R CODE</i> CÓDIGO ALFA'R	
							GRUPO		
							63X	A-CAB-63X-50	
Ω	<i>center cond.</i>	cond. central	<i>dielectric</i>	dieléctrico	<i>screen</i>	pantalla	<i>jacket</i>		
	material	\emptyset	material	\emptyset	material	\emptyset	material	\emptyset	
50±0.5	Cu	1.63 [.064]	PTFE	5.31 [.209]	Cu	6.35 [.250]	--	--	

GHz	1	2	4	7	10	20
dB/100mts	22	32	50	70	85	120
Watts	1100	800	500	360	300	200